

HINDI 880 LINEAR

• 100% acciaio
• 100% alluminio
• 100% acciaio
• 100% alluminio
• 100% acciaio



FADINI
The gate opener

Oil-hydraulic operator for double swinging gates

8800-000 is a double-acting oil-hydraulic operator for double swinging gates. It is designed to operate gates up to 100 m long and 10 m high. The operator is available in two different models and the hydraulic system is designed to operate gates up to 100 m long and 10 m high. The operator is available in two different models and the hydraulic system is designed to operate gates up to 100 m long and 10 m high. The operator is available in two different models and the hydraulic system is designed to operate gates up to 100 m long and 10 m high.

The operator is available in two different models and the hydraulic system is designed to operate gates up to 100 m long and 10 m high. The operator is available in two different models and the hydraulic system is designed to operate gates up to 100 m long and 10 m high. The operator is available in two different models and the hydraulic system is designed to operate gates up to 100 m long and 10 m high.

Both models are suitable for different gate weights and can be used for gates up to 100 m long and 10 m high. The operator is available in two different models and the hydraulic system is designed to operate gates up to 100 m long and 10 m high. The operator is available in two different models and the hydraulic system is designed to operate gates up to 100 m long and 10 m high.

Both models are suitable for different gate weights and can be used for gates up to 100 m long and 10 m high. The operator is available in two different models and the hydraulic system is designed to operate gates up to 100 m long and 10 m high. The operator is available in two different models and the hydraulic system is designed to operate gates up to 100 m long and 10 m high.





With our battery operation, an electric actuator will allow you to open and close your gate quickly.

- Easy and Simple Installation
- Fast and Safe Operation



Components Steel 800 Series

- | | |
|---------------------------------------|--------------------------------------|
| 1. Control Unit (with Remote Control) | 10. Clear battery cabinet |
| 2. 24V capacitor motor unit | 11. Top rail (with 800 Series) |
| 3. Steel rail (with bracket) | 12. Side rail (with bracket) |
| 4. Automatic safety sensor | 13. Motor bracket |
| 5. Remote control (optional) | 14. 24V power transformer (optional) |
| 6. 24V battery power | |

HINDI BBO GATE OPERATOR

Technical specifications

GENERAL DATA

Model: BBO
 Voltage: 230V AC
 Frequency: 50/60 Hz
 Power: 1000W
 Weight: 1.5kg
 Dimensions: 100x100x100mm

TECHNICAL DATA

Motor: 1000W
 Gear: 1:1
 Speed: 100 RPM
 Torque: 10 Nm
 Protection: IP44
 Material: Aluminum
 Color: Silver

ACCESSORIES

Remote control: BBO-RC
 Receiver: BBO-RCV
 Battery: BBO-BAT

Kit package



CE **CONFORME A LA NORME CEI EN 12445**

Il è vietato l'uso non autorizzato di questo prodotto. È vietata la ristampa o l'uso non autorizzato senza permesso scritto dalla FADINI.

